

# Internet Email

---

## email

- 1. n. Electronic mail automatically passed through computer networks and/or via modems over common-carrier lines.
- 2. vt. To send electronic mail.
- 3. French n. A hard enamel obtained by heating special paints in a furnace

## emailed

- 1. vt. Sent electronic mail.
  - 2. adj. Embossed (with a raised pattern) or perhaps arranged in a net or open work.
-

# Overview

---


- Before The Internet: Isolation and Early Contact
- The Agents And Their Assignments
- SMTP: Pass It On
- Basic Text Message Format: Opening The Envelope
- Post Office Protocol
  
- MIME: See Attached
- IMAP: Full Mailbox Control

# Pre-Internet: The Dark Ages of Isolation

---

## Intra-Office Email Systems

- Lotus Notes, Novell Groupware, Microsoft Exchange
- even Unix



- ISO X.400 - Email by Committee

# UUCP: Early Contact

---


- Unix-to-Unix Copy
- Machines dial each other
- Store and Forward
- Each machine only knows a few others
- Bang Paths

Direct lineage to both USENET and SMTP

# The Agents and their Assignments

---

- (MUA) Mail User Agent
  - Pine, Mutt, Elm, Eudora, Outlook
- (MTA) Mail Transport Agent
  - Sendmail, Exim, Postfix, Qmail
- (MDA) Mail Delivery Agent
  - /bin/mail, mail.local, deliver, procmail



# SMTP: Pass It On

---

Simple Mail Transport Protocol - RFC 821 (1982)

- Relay message to another MTA
  - And then another...
    - And then another...
- Envelope - Sender and Recipient addresses
- Semi-Opaque Data inside
- End data with lone ".", double any existing lone "."
- First MTA adds Date and Message-ID headers if not already there
- Each MTA adds Received header identifying itself
- TCP port 25

# SMTP Session

---

```
220 server.funknet.net ESMTP Sendmail
HELO client.funknet.net
250 server.funknet.net Hello client.funknet.net
MAIL FROM: <rfunk@funknet.net>
250 <rfunk@funknet.net> sender ok
RCPT TO:<cantonlinux@yahoogroups.com>
250 <cantonlinux@yahoogroups.com> recipient ok
RCPT TO:<colug@colug.net>
250 <colug@colug.net> recipient ok
DATA
354 Enter message, ending with "." on a line by itself
Subject: hi!
```

```
hey there
```

```
250 OK Got Message
```

```
QUIT
```

```
221 server.funknet.net closing connection
```

---

# Basic Text Message Format - RFC 822

---

## ■ Address Format

- Bare: rfunk@funknet.net
- Comments: rfunk@funknet.net (Robert M. Funk)
- Brackets: Rob Funk <rfunk@funknet.net>
- Quotes: "Robert M. Funk" <rfunk@funknet.net>

## ■ Must be able to pass through old/weird gateways

- 7-bit ASCII Text
- More than 256 chars/line risks cutoff

## ■ Headers

- Name: value
- Initial blank continues previous line

## ■ Body

- Blank line separates from headers



# Post Office Protocol version 3

---

POP3 - For recipients with intermittent connections

- USER rfunc
- PASS MyPasWrd
  
- STAT
  - Get number of messages and total size
- LIST [1]
  - List message numbers and sizes
  
- LAST
  - (obsoleted) Get last message number seen
- UIDL [1]
  - List unique IDs of messages, for client-side tracking

# Post Office Protocol version 3

---

- RETR 1

- Retrieve message 1

- TOP 6 2

- Get the headers and first 2 body lines of message 6

- RSET

- unmark deletions

- QUIT